Pollak

300 Dan Road Canton, MA 02021

Phone: 781.830.0340 • Fax: 781.575.8964

Email: jerry.bober@stoneridge.com • Web Address:www.pollakaftermarket.com

Item # 51-904, Battery Master Disconnect Switches



Battery Master Disconnect Switches

Master Disconnect Switches designed for 12 VDC vehicles (Truck, Automotive, Marine, RV) to disconnect all circuitry to reduce possibility of theft and accidental electrical fires. Available in keyed or lever versions, with or without indexing pins, and various sizes of terminal studs. Lever Operated - 6-36 Volt D.P.S.T. (Off-On) Four Stud Terminals

SPECIFICATIONS

Features	Incorporated heavy duty silver plated contacts. One piece die-cast housing sealed with O-rings at base and mounting stem to keep out dust and moisture. Two 3/4" and two No 10-32 copper alloy stud terminals hexnuts and lock washer.
Specification	Rating: Continous Rating (Make Break), Large Studs -180 Amps, Small Studs - 20 Amps, Intermittent Rating (Carrying), Large Studs - 1000 Amps (20 sec. "On" - 5 Minutes "Off")
Applications	For battery and alternator or generator field circuit. Designed to break alternator generator circuit prior to battery circuit disconnect.